


212 negatives Reduzierstück



DIN EN 10241
ISO 228-1G

Wst. 316

Abnahmeprüfzeugnis
gem. EN 10204-3.1

Auch in gedrehter Ausführung lieferbar !



inch	inch	DN mm	DN mm	L mm	SW mm	Ausf.	Artikel-Nr.
1/4"	1/8"	8	6	27,0	17	guss	212
3/8"	1/8"	10	6	29,0	21	guss	212
3/8"	1/4"	10	8	30,5	21	guss	212
1/2"	1/8"	15	6	32,5	26	guss	212
1/2"	1/4"	15	8	34,0	26	guss	212
1/2"	3/8"	15	10	34,5	26	guss	212
3/4"	1/8"	20	6	33,5	32	guss	212
3/4"	1/4"	20	8	35,0	32	guss	212
3/4"	3/8"	20	10	35,5	32	guss	212
3/4"	1/2"	20	15	38,5	32	guss	212
1"	1/8"	25	6	36,5	38	guss	212
1"	1/4"	25	8	38	38	guss	212
1"	3/8"	25	10	38,5	38	guss	212
1"	1/2"	25	15	41,0	38	guss	212
1"	3/4"	25	20	44,0	38	guss	212
1.1/4"	1/4"	32	8	40,0	50	guss	212
1.1/4"	3/8"	32	10	40,0	50	guss	212
1.1/4"	1/2"	32	15	42,5	50	guss	212
1.1/4"	3/4"	32	20	45,0	50	guss	212
1.1/4"	1"	32	25	47,0	50	guss	212
1.1/2"	1/4"	40	8	41,0	54	guss	212
1.1/2"	3/8"	40	10	42,0	54	guss	212
1.1/2"	1/2"	40	15	45,0	54	guss	212
1.1/2"	3/4"	40	20	46,0	54	guss	212
1.1/2"	1"	40	25	48,0	54	guss	212
1.1/2"	1.1/4"	40	32	50,0	54	guss	212
2"	1/4"	50	8	44,5	68	guss	212
2"	3/8"	50	10	31,0	68	guss	212
2"	1/2"	50	15	9,0	68	guss	212
2"	3/4"	50	20	51,0	68	guss	212
2"	1"	50	25	51,0	68	guss	212
2"	1.1/4"	50	32	53,0	68	guss	212
2"	1.1/2"	50	40	54,0	68	guss	212

* Auch in gedrehter Ausführung lieferbar!