


235 6kt-Stopfen konisch



DIN EN 10241
ISO 228-1A

Wst. 316

Abnahmeprüfzeugnis
gem. EN 10204-3.1


Auch in gedrehter Ausführung lieferbar !



inch	DN mm	L mm	SW mm	Ausf.	Artikel-Nr.
1/8"	6	17	12	guss	235
1/4"	8	17,5	16	guss	235
3/8"	10	18	20	guss	235
1/2"	15	25	24	guss	235
3/4"	20	26	30	guss	235
1"	25	29	38	guss	235
1.1/4"	32	35	46	guss	235
1.1/2"	40	38	52	guss	235
2"	50	39	65	guss	235
2.1/2"	65	44	84	guss	235
3"	80	54	94	guss	235
4"	100	55	119	guss	235

* Auch in gedrehter Ausführung lieferbar!

236 6kt-Stopfen zylindrisch



DIN EN 10241
ISO 228-1G

Wst. 316

Abnahmeprüfzeugnis
gem. EN 10204-3.1

Auch in gedrehter Ausführung lieferbar !



inch	DN mm	L mm	SW mm	Ausf.	Artikel-Nr.
1/8	6	17	12	guss	236
1/4	8	17,5	16	guss	236
3/8	10	18	20	guss	236
1/2	15	25	24	guss	236
3/4	20	26	30	guss	236
1	25	29	38	guss	236
1.1/4	32	35	46	guss	236
1.1/2	40	38	52	guss	236
2	50	39	65	guss	236
2.1/2	65	44	84	guss	236
3	80	54	94	guss	236
4	100	55	119	guss	236

* Auch in gedrehter Ausführung lieferbar!