


238 4kt-Stopfen konisch



DIN EN 10241

Wst. 316

Abnahmeprüfzeugnis
gem. EN 10204-3.1


Auch in gedrehter Ausführung lieferbar !



inch	DN mm	L2 mm	SW mm	Ausf.	Artikel-Nr.
1/8"	6	16,5	6	guss	238
1/4"	8	20	9	guss	238
3/8"	10	24	11	guss	238
1/2"	15	25	13	guss	238
3/4"	20	27	16	guss	238
1"	25	32	20	guss	238
1.1/4"	32	35	24	guss	238
1.1/2"	40	36	25	guss	238
2"	50	38	32	guss	238
2.1/2"	65	48	42	guss	238
3"	80	52	46	guss	238
4"	100	62	58	guss	238

* Auch in gedrehter Ausführung lieferbar!

237 4kt-Stopfen zylindrisch



DIN EN 10241
ISO 228-1A

Gedreht: Wst. 1.4571 / TP 316Ti
Gedreht: Wst. 1.4404 / TP 316/316L

Abnahmeprüfzeugnis
gem. EN 10204-3.1



inch	DN mm	L1 mm	L2 mm	D mm	SW mm	Ausf.	Artikel-Nr.
1"	25	14	27	39,5	20	gedreht	237
1.1/4"	32	19	33	49,5	22	gedreht	237
1.1/2"	40	20	35	59,0	25	gedreht	237
2"	50	21	36	70,0	30	gedreht	237
2.1/2"	65	25	42	88,0	40	gedreht	237
3"	80	25	42	100,0	45	gedreht	237