


Rundstahlbügel DIN 3570



Form A

ohne Mutter u. Schrauben
Maße nach DIN 3570

Wst. 1.4571 / TP 316Ti
Wst. 1.4404 / TP 316/316L
Wst. 1.4307/ TP 304/304L

Abnahmeprüfzeugnis
gem. EN 10204-3.1 f.d.Vormaterial



DN	d1	a1	b2	d3	e	h	GEWICHT
mm	mm	mm		Gewinde	Gewinde		Kg/St.
15		25	35	M10	35	65	6,0
20	25,0	30	40	M10	40	70	7,4
20	26,9	30	40	M10	40	70	7,4
25	30,0	38	40	M10	48	76	8,1
25	33,7	38	40	M10	48	76	8,1
32	38,0	46	50	M10	56	86	9,4
32	42,4	46	50	M10	56	86	9,4
40	44,5	52	50	M10	62	92	10,2
40	48,3	52	50	M10	62	92	10,2
50	57,0	64	50	M12	76	109	17,0
50	60,3	64	50	M12	76	109	17,0
65	76,1	82	50	M12	94	125	20,3
80	88,9	94	50	M12	106	138	22,6
100	108,0	120	60	M16	136	171	52
100	114,3	120	60	M16	136	171	52
125	133,0	148	60	M16	164	191	60
125	139,7	148	60	M16	164	191	60
125	159,0	176	60	M16	192	217	68
125	168,3	176	60	M16	192	217	68
175	191,0	202	60	M16	218	249	79
175	193,7	202	60	M16	218	249	79
200	216,0	228	70	M20	248	283	136
200	219,1	228	70	M20	248	283	136
250	267,0	282	70	M20	302	334	163
250	273,0	282	70	M20	302	334	163
300	318,0	332	70	M20	352	385	190
300	323,9	332	70	M20	352	385	190
350	355,6	378	70	M24	402	435	311
350	368,0	378	70	M24	402	435	311
400	406,4	428	70	M24	452	487	350
400	419,0	428	70	M24	452	487	350
500	508,0	530	70	M24	554	589	381
500	521,0	530	70	M24	554	589	381