


T-Stück reduziert EN 10253-4 Typ A, ASTM-A 403 ASME B16.9




geschw./nahtlos
gem. EN 10253-4
gem. ASTM A 403 / ASME B16.9
Wst. 1.4571 / TP 316Ti
Wst. 1.4404 / TP 316/316L
Wst. 1.4541 / TP 321
Wst. 1.4301/07 / TP 304/304L
Abnahmeprüfzeugnis
gem. EN 10204-3.1



AD1 mm	AD2 mm	S1 mm	S2 mm	a mm	b mm	ASTM Dimension	L mm	GEWICHT Kg/St	geschw. g	nahtlos n
26,67	21,34	2,1	2,1	29,0	29,0	3/4" x 1/2" SCH 10S	58,0	0,08	g	n
26,67	21,34	2,9	2,8	29,0	29,0	3/4" x 1/2" SCH 40S	58,0	0,12	g	n
26,67	21,34	3,9	3,7	29,0	29,0	3/4" x 1/2" SCH 80S	58,0	0,15		n
26,90	21,30	2,3	2,0	29,0	29,0		58,0	0,15	g	
26,90	21,30	2,9	2,6	29,0	29,0		58,0	0,18	g	
26,90	21,30	4,0	3,6	29,0	29,0		58,0	0,22		n
33,40	21,34	2,8	2,1	38,0	38,0	1" x 1/2" SCH 10S	76,0	0,19	g	n
33,40	21,34	3,4	2,8	38,0	38,0	1" x 1/2" SCH 40S	76,0	0,22	g	n
33,40	21,34	4,6	3,7	38,0	38,0	1" x 1/2" SCH 80S	76,0	0,28		n
33,40	26,67	2,8	2,1	38,0	38,0	1" x 3/4" SCH 10S	76,0	0,19	g	n
33,40	26,67	3,4	2,9	38,0	38,0	1" x 3/4" SCH 40S	76,0	0,23	g	n
33,70	21,30	2,0	2,0	38,0	38,0		76,0	0,18		n
33,70	26,90	2,0	2,0	38,0	38,0		76,0	0,19	g	
33,70	26,90	2,6	2,3	38,0	38,0		76,0	0,28	g	
33,70	21,30	2,6	2,3	38,0	38,0		76,0	0,28	g	
33,70	26,90	3,6	2,9	38,0	38,0		76,0	0,35	g	
33,70	21,30	3,6	2,9	38,0	38,0		76,0	0,35	g	
33,70	26,90	3,6	2,9	38,0	38,0		76,0	0,35	g	
33,70	21,30	3,6	2,9	38,0	38,0		76,0	0,35	g	
33,70	26,90	4,5	4,0	38,0	38,0		76,0	0,40	g	
33,70	21,30	4,5	4,0	38,0	38,0		76,0	0,40		n
42,16	21,34	2,8	2,1	38,0	38,0	1.1/4" x 1/2" SCH 10S	76,0	0,29	g	n
42,16	21,34	3,6	2,8	48,0	48,0	1.1/4" x 1/2" SCH 40S	96,0	0,37	g	n
42,16	26,67	2,8	2,1	48,0	48,0	1.1/4" x 3/4" SCH 10S	96,0	0,29	g	n
42,16	26,67	3,6	2,9	48,0	48,0	1.1/4" x 3/4" SCH 40S	96,0	0,37	g	n
42,16	33,40	2,8	2,8	48,0	48,0	1.1/4" x 1" SCH 10S	96,0	0,31	g	n
42,16	33,40	3,6	3,4	48,0	48,0	1.1/4" x 1" SCH 40S	96,0	0,39	g	n
42,16	33,40	4,9	4,6	48,0	48,0	1.1/4" x 1" SCH 80S	96,0	0,51		n
42,40	26,90	2,0	2,0	48,0	48,0		96,0	0,30		n
42,40	33,70	2,0	2,0	48,0	48,0		96,0	0,30	g	
42,40	33,70	2,6	2,6	48,0	48,0		96,0	0,42	g	
42,40	26,90	2,6	2,3	48,0	48,0		96,0	0,38	g	
42,40	33,70	3,6	3,6	48,0	48,0		96,0	0,55	g	
42,40	26,90	3,6	2,9	48,0	48,0		96,0	0,52		n
48,26	21,34	2,8	2,1	57,0	57,0	1.1/2" x 1/2" SCH 10S	114,0	0,39	g	n
48,26	21,34	3,7	2,8	57,0	57,0	1.1/2" x 1/2" SCH 40S	114,0	0,51	g	n
48,26	21,34	5,1	3,7	57,0	57,0	1.1/2" x 1/2" SCH 80S	114,0	0,67		n
48,26	26,67	2,8	2,1	57,0	57,0	1.1/2" x 3/4" SCH 10S	114,0	0,40	g	n
48,26	26,67	3,7	2,9	57,0	57,0	1.1/2" x 3/4" SCH 40S	114,0	0,52	g	n
48,26	26,67	5,1	3,9	57,0	57,0	1.1/2" x 3/4" SCH 80S	114,0	0,69		n
48,26	33,40	2,8	2,8	57,0	57,0	1.1/2" x 1" SCH 10S	114,0	0,42	g	n
48,26	33,40	3,7	3,4	57,0	57,0	1.1/2" x 1" SCH 40S	114,0	0,55	g	n
48,26	33,40	5,1	4,6	57,0	57,0	1.1/2" x 1" SCH 80S	114,0	0,73		n
48,26	42,16	2,8	2,8	57,0	57,0	1.1/2" x 1.1/4" SCH 10S	114,0	0,44	g	n
48,26	42,16	3,7	3,6	57,0	57,0	1.1/2" x 1.1/4" SCH 40S	114,0	0,57	g	n
48,26	42,16	5,1	4,9	57,0	57,0	1.1/2" x 1.1/4" SCH 80S	114,0	0,77		n
48,30	26,90	2,0	2,0	57,0	57,0		114,0	0,41		n
48,30	33,70	2,0	2,0	57,0	57,0		114,0	0,41		n
48,30	42,40	2,0	2,0	57,0	52,0		114,0	0,43	g	
48,30	33,70	2,6	2,6	57,0	57,0		114,0	0,61	g	
48,30	26,90	2,6	2,3	57,0	57,0		114,0	0,54	g	

T-Stück reduziert EN 10253-4 Typ A, ASTM-A 403 ASME B16.9




geschw./nahtlos
gem. EN 10253-4
gem. ASTM A 403 / ASME B16.9
Wst. 1.4571 / TP 316Ti
Wst. 1.4404 / TP 316/316L
Wst. 1.4541 / TP 321
Wst. 1.4301/07 / TP 304/304L
Abnahmeprüfzeugnis
gem. EN 10204-3.1



AD1 mm	AD2 mm	S1 mm	S2 mm	a mm	b mm	ASTM Dimension	L mm	GEWICHT Kg/St	geschw. g	nahtlos n
48,30	26,90	3,6	2,9	57,0	57,0		114,0	0,73	g	
48,30	33,70	5,1	4,5	57,0	57,0		114,0	1,05		n
60,30	26,90	2,0	2,0	64,0	44,0		128,0	0,50		n
60,30	33,70	2,0	2,0	64,0	51,0		128,0	0,51		n
60,30	48,30	2,0	2,0	64,0	60,0		128,0	0,55		g
60,30	48,30	2,6	2,0	64,0	60,0		128,0	0,76	g	
60,30	42,40	2,6	2,0	64,	57,0		128,0	0,76	g	
60,30	33,70	2,6	2,0	64,0	51,0		128,0	0,72	g	
60,30	26,90	2,6	2,0	64,0	45,0		128,0	0,72	g	
60,30	21,30	2,6	2,0	64,0	45,0		128,0	0,72	g	
60,30	48,30	4,0	3,6	64,0	60,0		128,0	1,10	g	
60,30	33,70	4,0	3,6	64,0	51,0		128,0	1,09	g	
60,30	33,70	5,6	4,5	64,0	51,0		28,0	1,40	g	
60,33	21,34	2,8	2,1	64,0	64,0	2" x 1/2" SCH 10S	128,0	0,54	g	n
60,33	21,34	3,9	2,8	64,0	64,0	2" x 1/2" SCH 40S	128,0	0,74	g	n
60,33	26,67	2,8	2,1	64,0	64,0	2" x 3/4" SCH 10S	128,0	0,54	g	n
60,33	26,67	3,9	2,9	64,0	64,0	2" x 3/4" SCH 40S	128,0	0,74	g	n
60,33	33,40	2,8	2,8	64,0	64,0	2" x 1" SCH 10S	128,0	0,54	g	n
60,33	33,40	3,9	3,4	64,0	64,0	2" x 1" SCH 40S	128,0	0,74	g	n
60,33	42,16	2,8	2,8	64,0	64,0	2" x 1.1/4" SCH 10S	128,0	0,57	g	n
60,33	42,16	3,9	3,6	64,0	64,0	2" x 1.1/4" SCH 40S	128,0	0,80	g	n
60,33	48,26	2,8	2,8	64,0	64,0	2" x 1.1/2" SCH 10S	128,0	0,59	g	n
60,33	48,26	3,9	3,7	64,0	64,0	2" x 1.1/2" SCH 40S	128,0	0,83	g	n
60,33	48,26	5,5	5,1	64,0	64,0	2" x 1.1/2" SCH 80S	128,0	1,11		n
73,03	60,33	3,1	2,8	76,0	76,0	2.1/2" x 2" SCH 10S	152,0	0,94	g	n
73,03	60,33	5,2	3,9	76,0	76,0	2.1/2" x 2" SCH 40S	152,0	1,53	g	n
76,10	60,30	2,9	2,9	76,0	70,0		152,0	1,20		n
76,10	48,30	2,9	2,6	76,0	67,0		152,0	1,16		n
76,10	42,40	2,9	2,6	76,0	64,0		152,0	1,12		n
76,10	60,30	5,6	4,0	76,0	70,0		152,0	2,20		n
76,10	48,30	5,6	3,6	76,0	67,0		152,0	2,10		n
76,10	42,40	5,6	3,6	76,0	64,0		152,0	2,10		n
88,90	60,30	2,6	2,0	86,0	76,0		172,0	1,02	g	
88,90	76,10	3,2	2,9	86,0	83,0		172,0	1,85		n
88,90	60,30	3,2	2,	86,0	76,0		172,0	1,85		n
88,90	48,30	3,2	2,6	86,0	73,0		172,0	1,70		n
88,90	60,30	5,6	4,0	86,0	76,0		172,0	2,90		n
88,90	48,30	5,6	3,6	86,0	73,0		172,0	2,80		n
88,90	60,30	7,6	5,6	86,0	76,0		172,0	4,00		n
88,90	33,40	3,1	2,8	86,0	86,0	3" x 1" SCH 10S	172,0	1,08	g	n
88,90	33,40	5,5	3,4	86,0	86,0	3" x 1" SCH 40S	172,0	1,94	g	n
88,90	48,26	3,1	2,8	86,0	86,0	3" x 1.1/2" SCH 10S	172,0	1,19	g	n
88,90	48,26	5,5	3,7	86,0	86,0	3" x 1.1/2" SCH 40S	172,0	2,05	g	n
88,90	60,33	3,1	2,8	86,0	86,0	3" x 2" SCH 10S	172,0	1,23	g	n
88,90	60,33	5,5	3,9	86,0	86,0	3" x 2" SCH 40S	172,0	2,16	g	n
88,90	60,33	7,6	5,5	86,0	86,0	3" x 2" SCH 80S	172,0	2,85		n
114,30	88,90	2,9	2,6	105,0	98,0		210,0	3,00		n
114,30	76,10	2,9	2,6	105,0	95,0		210,0	3,00		n
114,30	60,30	2,9	2,6	105,0	89,0		210,0	2,90		n
114,30	88,90	6,30	5,6	105,0	98,0		210,0	5,10		n
114,30	60,30	6,30	4,0	105,0	89,0		210,0	4,85		n

T-Stück reduziert EN 10253-4 Typ A, ASTM-A 403 ASME B16.9



geschw./nahtlos
gem. EN 10253-4
gem. ASTM A 403 / ASME B16.9
Wst. 1.4571 / TP 316Ti
Wst. 1.4404 / TP 316/316L
Wst. 1.4541 / TP 321
Wst. 1.4301/07 / TP 304/304L
Abnahmeprüfzeugnis
gem. EN 10204-3.1



AD1 mm	AD2 mm	S1 mm	S2 mm	a mm	b mm	ASTM Dimension	L mm	GEWICHT Kg/St	geschw. g	nahtlos n
114,30	60,30	8,80	5,6	105,0	89,0		210,0	6,60		n
114,30	60,33	3,1	2,8	114,0	114,0	4" x 2" SCH 10S	228,0	1,88	g	n
114,30	60,33	6,0	3,9	114,0	114,0	4" x 2" SCH40S	228,0	3,52	g	n
114,30	88,90	3,1	3,1	114,0	114,0	4" x 3" SCH 10S	228,0	3,02	g	n
114,30	88,90	6,0	5,5	114,0	114,0	4" x 3" SCH 40S	228,0	3,83	g	n
168,28	88,90	3,4	3,1	143,0	143,0	6" x 3" SCH10S	286,0	4,21	g	n
168,28	88,90	7,11	5,5	143,0	143,0	6" x 3" SCH40S	286,0	8,52	g	n
168,28	114,30	3,40	3,1	143,0	143,0	6" x 4" SCH 10S	286,0	4,34	g	n
168,30	114,3	4,50	3,6	143,0	130,0		286,0	7,00		n
168,30	88,90	4,50	3,2	143,0	124,0		286,0	7,00		n
168,30	114,30	7,10	6,3	143,0	130,0		286,0	10,70		n
168,30	88,90	7,10	5,6	143,0	124,0		286,0	10,40		n
219,08	114,30	3,40	3,1	178,0	178,0	8" x 4" SCH10S	356,0	7,48	g	n
219,08	168,3	3,76	3,4	178,0	178,0	8" x 6" SCH 10S	356,0	7,91	g	n
219,08	168,28	8,18	7,1	178,0	178,0	8" x 6" SCH 40S	356,0	16,80	g	n
273,05	168,28	4,19	3,4			10" x 6" SCH 10S		12,80	g	
273,05	219,08	4,19	3,8			10" x 8" SCH 10S		13,30	g	
273,05	219,08	9,27	8,2			10" x 8" SCH 40S		28,90	g	
323,85	273,05	4,57	3,8			12" x 8" SCH 10S		19,60	g	
323,85	273,05	9,53	8,2			12" x 8" SCH 40S		40,30	g	
323,85	273,05	4,57	4,2			12" x 10" SCH 10S		20,50	g	
323,85	273,05	9,53	9,3			12" x 10" SCH 40S		42,30	g	